




**MODELL**  
CBY

**A nach B und B nach A**  
**EINSCHRAUBBOHRUNG: T-3A**



Relief, A to B and B to A High Capacity



**TECHNISCHE DATEN**

Gehäusotyp	Sandwich
Lochbild	ISO 05
Gehäuseeigenschaften	A nach B und B nach A
Verkettungshöhe	62 mm
Einschraubbohrung	T-3A
Open Cavities	2

**KONFIGURATION ÄNDERN**

(none) Modifier 6061-T651  
Aluminum, Buna-N

**KOMPONENTEN**

Part	Beschreibung	Anzahl
500-001-014	O-Ring	5

**BEMERKUNGEN**

**Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

**CONFIGURATION OPTIONS**

**MODIFIER**

Standard Options	Modifier	Material/Finish
/S	6061-T651 Aluminum, Buna-N	
/V	65-45-12 Ductile Iron, Buna-N, Blackened	
/N	6061-T651 Aluminum, Viton	
/Y	65-45-12 Ductile Iron, Viton, Blackened	

**MANIFOLD FACES**

**FACE GRID**

1	2	3	4
5	6	7	8
9	10	11	12

## **Face 2**

□

## **Face 6**

□

## **Face 7**

□

## **Face 8**

□

## **Face 10**

□

Copyright © 2002-2014 Sun Hydraulics Corporation. All rights reserved.